



TRACK USED IS LIGHTOLIER 6108NWH, 6101NWH, AND 6149NWH

DATE

JOB NAME

TYPE

Features **Applications**

- Small profile providing continuous uplight
- Uses dimmable LED modules
- Track on bottom of extrusion

- Office Areas
- Perimeters
- Retail stores
- Corridors
- Libraries

Series **Size** **LED System** **Color Temp** **Voltage** **Mounting** **Options**

| | | | | | | |
|----------------|---|---|----------------------------------|-------------------|--------------------------------------|---|
| TRX LED | | | | | | |
| | 2FT 4FT 8FT XFT (CONTINUOUS ROW MOUNTING) | LTG1- Standard LTG2- Low LTG3- High C- Custom Package (Consult Factory) | 3000K 3500K 4000K 5000K | 120 277 UNV | SM-Surface Mount PS- Pendant Stem | EM-Emergency Pack DB- Standard 10% Dimming Driver (0-10V) DB1%- 1% Dimming Driver (0-10V) LUTRON 2- Hi-Lume Dimming Driver (1% 2-wire control) LUTRON 3- Hi-Lume Dimming Driver (1% 3-wire control) |

Ordering Example: TRX LED-8FT-LTG3-4000K-UNV-DB

LED System Information

Options:

| NOMINAL PACKAGE | NOMINAL SYSTEM WATTS | NOMINAL DELIVERED LUMENS |
|-----------------|----------------------|--------------------------|
| LTG1 (STANDARD) | 35W (per 4ft) | 3200Lm (per 4ft) |
| LTG2 (LOW) | 25W (per 4ft) | 2320Lm (per 4ft) |
| LTG3 (HIGH) | 38W (per 4ft) | 3490Lm (per 4ft) |

Color Temperature Pro-rate:

| CCT | OUTPUT |
|-------|--------|
| 2700K | 93% |
| 3000K | 95% |
| 3500K | 97% |
| 4000K | 100% |
| 5000K | 103% |

***FOR ANY CUSTOM LED PACKAGE REQUESTS CONSULT FACTORY

Details

Application Features: Single piece of high purity extruded aluminum with die-formed specular aluminum. Two circuit track installed into housing. 20 amp maximum for all track fixtures installed on a run of MicroSquare. 3 wire system at 120v, 60 hz per track circuit.


Construction: Extruded Aluminum Housing.

Finish: Powder-coated white, baked enamel. Custom colors available.

Electrical: Integral Driver

Approvals: Union made, UL listed, and manufactured in the US.

Options: Emergency Battery Backup, Dimming Ballast



BE AWARE THAT PROVIDING YOUR OWN TRACK YOU MUST USE LIGHTOLIER 6108NWH, 6101NWH, OR 6149NWH OR EXACT DIMENSION EQUIVELANT.