



DATE

JOB NAME

TYPE

Features	Applications
----------	--------------

- Shallow design
- Clear prismatic acrylic wraparound lens
- Continuous row mounting capability
- Easy re-lamping and re-ballasting
- Uses T8, T5, T5HO or T12 lamps

- Schools
- Retail Stores
- Office Areas
- Corridors
- Bathrooms
- Utility Areas

Series	Lamps	Watts	Voltage	Options
--------	-------	-------	---------	---------

A

Lamps

- 2
- 3
- 4

Watts

- 17WT8
- 14WT5
- 24WT5HO
- 40WT12
- 32WT8
- 32WT8-8' (Tandem)
- 28WT5
- 28WT5-8' (Tandem)
- 54WT5HO
- 54WT5HO-8' (Tandem)

Voltage

- 120
- 277
- UNV
(T12 DEDICATED VOLTAGE ONLY)

Options

- EM-Emergency Pack
- EM2-2 Light Emergency Pack
- DB-Dimming Ballast
- SC-Separate Circuit
- PS-Pendant Stems (6", 12", 24", 36", 48")
- WH-6' Whips

Ordering Example: A-4-32WT8-MV-EM

Details

Application Features: Specification grade, surface mounted luminaire with clear prismatic #12 pattern acrylic lens. For use in indoor applications where a T8, T5, T5HO, or T12 luminaire with maximum efficiency is required.

Construction: Precision-formed steel housing, Flattened knockouts are provided on ends for conduit attachment. Diffuser hinges from either side in a lift and shift manner and is self-centered for easy re-lamping and re-ballasting. Suitable for row mounting.

Finish: Powder painted white.

Approvals: Union made, UL Listed, and manufactured in the US.

Mounting: Mounting holes provided

Optics: Standard diffuser is clear acrylic with prismatic bottom and ribbed linear sides for even and low-glare illumination.

Options: Emergency Battery Backup, Dimming Ballast, Separate Circuit,

CROSS SECTION VIEWS:

