



DATE

JOB NAME

TYPE

Features	Applications
<ul style="list-style-type: none"> <li>• Great for perimeters</li> <li>• 91.4% efficient</li> <li>• Uses dimmable LED moduels</li> <li>• Comes standard with specular alluminum asymmetrical reflector and steel housing</li> </ul>	<ul style="list-style-type: none"> <li>• Office Areas</li> <li>• Retail Stores</li> <li>• Class Rooms</li> <li>• Libraries</li> <li>• Restaurants</li> </ul>

Series	Size	LED System	Color Temp	Voltage	Options
<b>CV1S LED</b>	<b>2FT</b> <b>4FT</b> <b>8FT</b> <b>XFT</b> (Custom lengths available)	<b>LTG1-</b> Standard <b>LTG2-</b> Low <b>LTG3-</b> High <b>C-</b> Custom Package (Consult Factory)	<b>2700K</b> <b>3000K</b> <b>3500K</b> <b>4000K</b> <b>5000K</b>	<b>120</b> <b>277</b> <b>UNV</b>	<b>EM-</b> Emergency Pack <b>DB-</b> Standard 10% Dimming Driver (0-10V) <b>DB1%-</b> 1% Dimming Driver (0-10V) <b>LUTRON 2-</b> Hi-Lume Dimming Driver (1% 2-wire control) <b>LUTRON 3-</b> Hi-Lume Dimming Driver (1% 3-wire control) <b>WR-</b> White Reflector

### LED System Information

**Options:**

NOMINAL PACKAGE	NOMINAL SYSTEM WATTS	NOMINAL DELIVERED LUMENS
<b>LTG1 (STANDARD)</b>	14W (per foot)	1250Lm (per foot)
<b>LTG2 (LOW)</b>	11W (per foot)	1005Lm (per foot)
<b>LTG3 (HIGH)</b>	17W (per foot)	1550Lm (per foot)

**Color Temperature Pro-rate:**

CCT	OUTPUT
2700K	93%
3000K	95%
3500K	97%
4000K	100%
5000K	103%

### Details

**Application Features:** Specification grade cove lighting fixture. For use in indoor applications where an LED cove light is required.

**Construction:** Die and brake formed, 20 ga. pre-painted white cold rolled steel housing. Aluminum specular silver reflector. Sufficient knock-outs are provided for convenience outlet, pull switch and flexible conduit attachment.

**Finish:** Pre-painted high reflective white.

**Electrical:** Integral Driver.

**Approvals:** ETL Listed and manufactured in the US

**Options:** Emergency Battery Backup, Dimming Ballast, and High-Reflectance White Optics Reflector

