



DATE

JOB NAME

TYPE

Features **Applications**

- Welded Steel Housing
- Uses Dimmable LED modules
- Clean appearance, no exposed fasteners.

- Hospitals
- Stairwells
- Corridors
- Fitting Rooms
- Stairwells
- Nursing Homes

Series	Size	LED System	Color Temp	Voltage	Options
CCU LED	2FT 4FT 8FT	LTG1- Standard LTG2- Low LTG3- High C- Custom Package (ie-C5400Lm))	3000K 3500K 4000K 5000K	120 277 UNV	EM-EM Pack DB- Dimming LDB3- Lutron Dimming Driver (1% 3-wire control) LDBD- Lutron Dimming Driver (1% Digital EcoSystem) SC-Separate Circuit

Ordering Example: CCU LED-4FT-LTG1-3500K-UNV-DB

LED System Information

Options:

NOMINAL PACKAGE	NOMINAL SYSTEM WATTS	NOMINAL DELIVERED LUMENS
LTG1 (STANDARD)	29.5W (per 4ft)	3665Lm (per 4ft)
LTG2 (LOW)	27W (per 4ft)	3245Lm (per 4ft)
LTG3 (HIGH)	33W (per 4ft)	4090m (per 4ft)

Color Temperature Pro-rate:

CCT	OUTPUT
3000K	95%
3500K	97%
4000K	100%
5000K	103%

***FOR ANY CUSTOM LED PACKAGE REQUESTS CONSULT FACTORY

Details

Application Features: Specification grade, surface mounted corner luminaire with clear prismatic #12 pattern acrylic lens. For use in indoor applications where a LED luminaire with maximum efficiency is required. Available in 2, 3, or 4 foot. Optional gasketing eliminates light leaks-suitable for row-mounting..

Construction: Die formed and spot welded, heavy gauge cold rolled steel housing. Spot welded for clean appearance; hinge is concealed.

Approvals: Union made, UL Listed, and manufactured in the US.

Optics: Opal white acrylic snap-in lens.

Options: Emergency Battery Backup (must specify voltage), Seperate circuit.

DISCLAIMER: CORONET INC RESERVES THE RIGHT TO MAKE ANY DESIGN CHANGES FOR CONTINUOUS IMPROVEMENT WHICH WILL NOT AFFECT THE OVERALL APPEARANCE OR PERFORMANCE. ALL CEILINGS ARE TO BE ADEQUATELY REINFORCED BY OTHERS BEFORE INSTALLATION. ALL FIXTURES ARE TO BE WIRED BY A CERTIFIED ELECTRICIAN ONLY. THIS INFORMATION IS PROPERTY OF CORONET INC., AND THE INFORMATION IT CONTAINS MAY NOT BE USED WITHOUT ANY WRITTEN CONSENT OF CORONET INC.

Model	A	B
2FT	24-1/4"	10-1/8"
3FT	36-1/4"	16-1/8"
4FT	48-1/4"	22-1/8"

