



DATE

JOB NAME

TYPE

| Features | Applications |
|---|---|
| <ul style="list-style-type: none"> • Opal white lens; .125" thick • Uses LED dimmable boards • Available for mounting in lay in T-bar and sheetrock ceilings | <ul style="list-style-type: none"> • Office Areas • Class Rooms • Retail Stores • Hospitals |

| Series | Size | LED System | Color Temp | Mounting | Lens | Options |
|----------------|------------|--|----------------------------------|------------------------------------|-----------------------------|--|
| RRD LED | 18" | LTG1- Standard LTG2- Low LTG3- High C- Custom Package (ex.-C4000Lm) | 2700K 3000K 3500K 4000K | T-Lay-in for T-Bar SR-Sheetrock | FLL- Flush RG- Regressed | EM- Emergency Pack DB- Standard 10% Dimming Driver (0-10V) DB1%- 1% Dimming Driver (0-10V) LUTRON 2- Hi-Lume Dimming Driver (1% 2-wire control) LUTRON 3- Hi-Lume Dimming Driver (1% 3-wire control) |

Ordering Example: RRD LED-18"-LTG2-4000K-T-FLL-DB

LED System Information

Options:

| NOMINAL PACKAGE | NOMINAL SYSTEM WATTS | NOMINAL DELIVERED LUMENS |
|-----------------|----------------------|--------------------------|
| LTG1 (STANDARD) | 28W | 2,350Lm |
| LTG2 (LOW) | 25W | 2,100Lm |
| LTG3 (HIGH) | 32W | 2,650Lm |

***FOR ANY CUSTOM LED PACKAGE REQUESTS CONSULT FACTORY

Color Temperature Pro-rate:

| CCT | OUTPUT |
|-------|--------|
| 2700K | 93% |
| 3000K | 95% |
| 3500K | 97% |
| 4000K | 100% |
| 5000K | 103% |

Details

Application Features: Specification grade, recessed troffer with formed circular lens. For use in indoor applications where a LED is required

Construction: Die formed and embossed, heavy gauge cold rolled steel housing. Spun steel trim.

Finish: Powder coated matte white.

Electrical: Integral Driver

Approvals: Union made, ETL listed, and manufactured in the US.

Mounting: Recessed mounting for T-Bar for sheetrock ceiling installation.

Optics: .125" thick concave opal lens

Options: Emergency Battery Backup, Dimming,

DISCLAIMER: CORONET INC RESERVES THE RIGHT TO MAKE ANY DESIGN CHANGES FOR CONTINUOUS IMPROVEMENT WHICH WILL NOT AFFECT THE OVERALL APPEARANCE OR PERFORMANCE. ALL CEILINGS ARE TO BE ADEQUATELY REINFORCED BY OTHERS BEFORE INSTALLATION. ALL FIXTURES ARE TO BE WIRED BY A CERTIFIED ELECTRICIAN ONLY. THIS INFORMATION IS PROPERTY OF CORONET INC., AND THE INFORMATION IT CONTAINS MAY NOT BE USED WITHOUT ANY WRITTEN CONSENT OF CORONET INC.

