



DATE _____

JOB NAME _____

TYPE _____

Features **Applications**

- | | |
|---|---|
| <ul style="list-style-type: none"> • Shallow design • Clear prismatic acrylic wraparound lens • Continuous row mounting capability | <ul style="list-style-type: none"> • Schools • Retail Stores • Office Areas • Corridors • Bathrooms • Utility Areas |
|---|---|

Series	Size	LED System	Color Temp	Voltage	Mounting	Options
A SERIES LED					SM	
	4FT 8FT	LTG1- Standard LTG2- Low LTG3- High C- Custom Package (Consult Factory)	3000K 3500K 4000K 5000K	120 277 UNV		EM- Emergency Pack DB- Dimming LDB3- Lutron Dimming Driver (1% 3-wire control) LDBD- Lutron Dimming Driver (1% Digital EcoSystem 4-wire control) PS- Pendant Stems (6", 12", 24", 36", 48") WH- Whips

Ordering Example: A SERIES LED-4FT-LTG2-4000K-UNV-SM-DB

LED System Information

Options:

NOMINAL PACKAGE	NOMINAL SYSTEM WATTS	NOMINAL DELIVERED LUMENS
LTG1 (STANDARD)	58W	6450Lm
LTG2 (LOW)	53W	5320Lm
LTG3 (HIGH)	64W	7365Lm

Color Temperature Pro-rate:

CCT	OUTPUT
3000K	95%
3500K	97%
4000K	100%
5000K	103%

***FOR ANY CUSTOM LED PACKAGE REQUESTS CONSULT FACTORY

Details

Application Features: Specification grade, surface mounted luminaire with milk white lens. For use in indoor applications where a LED luminaire with maximum efficiency is required.

Construction: Precision-formed steel housing. Flattened knockouts are provided on ends for conduit attachment. Diffuser hinges from either side in a lift and shift manner and is self-centered for easy re-lamping and re-ballasting. Suitable for row mounting.

Electrical: Integral driver.

Approvals: Union made, ETL listed, and manufactured in the US.

Mounting: Surface mounts over electrical junction box or with optional pendant stems.

Optics: Milk White Lens

Options: Emergency Battery Backup, Dimming, and 6' Whips.

