

DATE _____

JOB NAME _____

TYPE _____

Features **Applications**

- Clean appearance
- Wall bracket mounted
- Steel housing and ends caps with textured finish
- Uses LED dimmable modules

- Office Areas
- Retail Stores
- Class Rooms
- Libraries
- Restaurants

Series	Size	LED System	Color Temp	Voltage	Mounting	Options
1050WM LED	4FT (NOMINAL) 8FT (NOMINAL) XFT (CONTINUOUS ROW MOUNTING)	LTG1- Standard LTG2- Low LTG3- High C- Custom Package (Consult Factory)	3000K 3500K 4000K 5000K	120 277 UNV	WB—Wall Bracket	EM-EM Pack 1-Lamp DB-Dimming Ballast CC-Custom Color

Ordering Example: 1050WM LED-4FT-2LTG1-35000K-UNV-WB-EM

LED System Information

Options:

NOMINAL PACKAGE	NOMINAL SYSTEM WATTS	NOMINAL DELIVERED LUMENS
LTG1 (STANDARD)	35W (per 4ft)	3055Lm (per 4ft)
LTG2 (LOW)	33W (per 4ft)	2770Lm (per 4ft)
LTG3 (HIGH)	38W (per 4ft)	3260m (per 4ft)

Color Temperature Pro-rate:

CCT	OUTPUT
3000K	95%
3500K	97%
4000K	100%
5000K	103%

***FOR ANY CUSTOM LED PACKAGE REQUESTS CONSULT FACTORY

Details

Application Features: Specification grade, suspended, high performance architectural luminaire. For use in indoor applications where an LED direct/indirect luminaire with maximum uplight as well as glare-free downlight is required. Available as individual fixtures or with end and intermediate units for mounting in continuous rows. Fixtures designed to mount on 4 foot and 8 foot centers.

Construction: Durable cold rolled 20 ga. steel body. Sufficient knock-outs provided for connections and through wiring.

Finish: Pre-treated phosphate bonded (rust inhibitor), white powder coated finish.

Electrical: Integral Driver.

Approvals: UL Listed for damp location.

Optics: 95% enhanced anodized aluminum reflector and housing with slots with plastic overlay.


Options: Emergency Battery Backup, Dimming Ballast, Separate Circuit, Custom Colors, Spade End Caps.

Light Distribution:
Indirect-88% Direct-12%

FRONT VIEW




END VIEW



4' MODEL

TOP VIEW



8' MODEL

TOP VIEW

