



DATE

JOB NAME

TYPE

Features

- LED Industrial fixture
- Knock-outs provided for convenience outlet, pull switch and conduit attachment

Applications

- Office Areas
- Retail Stores
- Class Rooms
- Libraries

Series	Size	LED System	Color Temp	Voltage	Options
H LED	2ft 3ft 4ft 6ft 8ft	LTG1- Standard LTG2- Low LTG3- High C- Custom Package (Consult Factory)	3000K 3500K 4000K 5000K	120 277 UNV	EM—EM Pack DB—Dimming Ballast MS—Motion Sensor AS—Asymmetric Reflector WG—Wireguard CHR—Chrome Reflector VH—"V" Hangers

Ordering Example: H LED-4FT-LTG2-4000K-UNV-DB

LED System Information

Options:

NOMINAL PACKAGE	NOMINAL SYSTEM WATTS	NOMINAL DELIVERED LUMENS
LTG1 (STANDARD)	35W (per 4ft)	3,900Lm (per 4ft)
LTG2 (LOW)	33W (per 4ft)	3,570Lm (per 4ft)
LTG3 (HIGH)	38W (per 4ft)	4,360Lm (per 4ft)

Color Temperature Pro-rate:

CCT	OUTPUT
3000K	95%
3500K	97%
4000K	100%
5000K	103%

***FOR ANY CUSTOM LED PACKAGE REQUESTS CONSULT FACTORY

Details

Application Features: Specification grade fluorescent side socket channel For use in indoor applications where an LED strip with industrial reflector and low cost is required. Available in 2', 3', 4', 6' and 8' lengths.

Construction: Die formed 20 ga. cold rolled steel housing. Fixture components snap together for ease of installation and maintenance. Sufficient knock-outs provided for convenience outlet, pull switch and flexible conduit attachment.

Finish: High reflective white.

Electrical: Integral Driver

Approvals: Union made, ETL listed, and manufactured in the US

