

S LED (STANDARD STRIP)

coronet



DATE

JOB NAME

TYPE

Features

- Fixture components snap together for ease of installation and maintenance
- Knock-outs provided for convenience outlet, pull switch and conduit attachment

Applications

- Office Areas
- Retail Stores
- Class Rooms
- Libraries
- Restaurants

Series	Size	LED System	Color Temp	Voltage	Options
S LED	4FT	LTG1- Standard LTG2- Standard LTG3- Standard C- Custom Package (ie-C5000Lm)	2700K 3000K 3500K 4000K 5000K	120 277 UNV	EM-EM Pack Lamp ASYM-Asymmetric Reflector LUTRON 2- Hi-Lume Dimming Driver (1% 2-wire control) LUTRON 3- Hi-Lume Dimming Driver (1% 3-wire control)

Ordering Example: S LED-4FT-LTG1-4000K-UNV-ASYM

LED System Information

Options:

NOMINAL PACKAGE	NOMINAL SYSTEM WATTS	NOMINAL DELIVERED LUMENS
LTG1 (STANDARD)	35W (per 4ft)	3,900Lm (per 4ft)
LTG2 (LOW)	25W (per 4ft)	2,950Lm (per 4ft)
LTG3 (HIGH)	38W (per 4ft)	4,260Lm (per 4ft)

Color Temperature Pro-rate:

CCT	OUTPUT
2700K	93%
3000K	95%
3500K	97%
4000K	100%
5000K	103%

***FOR ANY CUSTOM LED PACKAGE REQUESTS CONSULT FACTORY

Details

Application Features: Specification grade fluorescent channel. For use in indoor applications where a LED striplight with tool-less design and low cost is required.

Construction: Die formed 20 ga. cold rolled steel housing. Fixture components snap together for ease of installation and maintenance. Sufficient knock-outs provided for convenience outlet, pull switch and flexible conduit attachment.

Finish: Baked white enamel.

Electronic: Integral Driver.

Approvals: Union made, UL listed, and manufactured in the US.

Options: Emergency Battery Backup, Dimming Ballast, Separate Circuit, Motion Sensor, Wireguard, Asymmetric Reflector, Symmetric Reflector.

S LED (STANDARD STRIP)

coronet

