



DATE

JOB NAME

TYPE

Features	Applications
<ul style="list-style-type: none"> • Single perforated metal lamp shield • Shallow design • 'Diffuser Only' Option • Clean appearance, no exposed fasteners 	<ul style="list-style-type: none"> • Office Areas • Retail Stores • Class Rooms • Corridors

Series	Size	Lamps	Watts	Voltage	Options
TSSW	2 X 2 2 X 4	2	14W T5 24W T5HO 28W T5 54W T5HO	120 277 UNV	EM-EM Pack DB-Dimming Ballast SC-Separate Circuit DO-Diffuser Only SP-Shallow Parabolic Louver (L31) AR—Air Return WH—6' Whips

Ordering Example: TSSW-2X4-2-28WT5-UNV-DB

Details

Application Features: Premium grade, recessed, high performance direct/indirect architectural luminaire with single perforated metal lamp shield and translucent acrylic diffuser. For use in indoor applications where a T5 or T5HO luminaire with soft, low-glare illumination and modern styling is required. Available in 2x2 and 2x4 configurations. Shallow design accommodates mounting in obstructed ceiling plenums.

Construction: Die formed and spot welded, 20 ga. cold rolled steel housing with precision formed, cold rolled steel reflector and die formed cold rolled steel perforated lamp shield with translucent acrylic diffuser. Sufficient knock-outs provided on back of housing for flexible conduit attachment.

Finish: Powder painted matte white.

Electrical: Electronic ballasts are class P, thermally protected.

Approvals: UL Listed for damp location.

Mounting: Recessed mounting for T-Bar, Slot Grid or with Flange Kit for sheetrock ceiling installations.

Optics: Arched reflector and translucent acrylic diffuser with perforated lamp shield.

Options: Emergency Battery Backup, Dimming Ballast, Separate Circuit, Diffuser Only, Shallow Parabolic Louver, Air Supply/Return Slots, 6' Whips.

67% efficient with metal lamp shield and diffuser
83% efficient with diffuser only



Model	A	B
2 X 2	23 3/4"	23 3/4"
2 X 4	23 3/4"	47 3/4"

