



DATE

JOB NAME

TYPE

Features	Applications
<ul style="list-style-type: none"> • 50,000 hour rated life • Color temp: 3,000K (warm white) • UL approved 	<ul style="list-style-type: none"> • Kitchens • Office Areas • Class Rooms • Libraries

Series	Size	Color Temp	Voltage
UC LED		3000K	120V

12"
18"
24"

Ordering Example: UCLED-18"-3000K-120V

LED System Information

Options:

SIZE	SYSTEM WATTS	DELIVERED LUMENS
12"	7W	250Lm
18"	10W	470Lm
24"	14W	640Lm

Details

Housing and Construction:

- Extruded Aluminum
- Standard Finish: Premium Powder Coated in White
- Sleek 1" Profile (3-1/2" Wide)
- Lens: Tempered Glass with Micro-Prismatic Texture

LEDs:

- Manufacturer: Nichia
- Rated Life: 50,000 hours
- Power: 1.6 Watt Max
- Color Temp: 3000K, Warm White, Comparable to Halogen

Driver:

- 120 Volt Input
- 12 Watt Max, Constant Current @ 380 mA
- UL 1310, Rated for Dry Location

Dimming:

- Lutron Skylark S-600P
- Diva DV-600P
- Ariadni AY-60P
- using 18" linking connector cords

Wiring and Switching:

- Convertible 120V input with either Direct Wire or Cord and Plug; Knockouts provided for either configuration
- Linkable between fixtures (when spacing between fixtures is desired) or double-ended connectors (for continuous fixture mounting); Maximum number of linked fixtures is 32
- Pre-Installed On/Off Rocker Switch

September 2014

Coronet Inc. | Phone: 973-345-7660 | Fax: 973-345-8705 | www.coronetled.com

UC LED

DISCLAIMER: CORONET INC RESERVES THE RIGHT TO MAKE ANY DESIGN CHANGES FOR CONTINUOUS IMPROVEMENT WHICH WILL NOT AFFECT THE OVERALL APPEARANCE OR PERFORMANCE. ALL CEILINGS ARE TO BE ADEQUATELY REINFORCED BY OTHERS BEFORE INSTALLATION. ALL FIXTURES ARE TO BE WIRED BY A CERTIFIED ELECTRICIAN ONLY. THIS INFORMATION IS PROPERTY OF CORONET INC., AND THE INFORMATION IT CONTAINS MAY NOT BE USED WITHOUT ANY WRITTEN CONSENT OF CORONET INC.