



DATE \_\_\_\_\_

JOB NAME \_\_\_\_\_

TYPE \_\_\_\_\_

**Features** **Applications**

- Single perforated metal lamp shield
- Translucent opal white acrylic overlay
- Clean appearance
- no exposed fasteners

- Office Areas
- Retail Stores
- Class Rooms
- Corridors

Series	Size	LED System	Color Temp	Voltage	Mounting	Options
<b>BPCW LED</b>	<b>2x4</b>	LTG1- Standard LTG2- Low LTG3- High C- Custom Package (Consult Factory)	3000K 3500K 4000K 5000K	120 277 UNV	SM-Surface Mount PS- Pendant Stem	EM-EM Pack* DB- Dimming SC-Separate Circuit WH- Whips

\* Voltage must be specified with EM option

Ordering Example: BPCW LED-2X4-LTG2-4000K-UNV-SM-DB

**LED System Information**

**Options:**

PACKAGE	SYSTEM WATTS	DELIVERED LUMENS
LTG1 (STANDARD)	58W	5415Lm
LTG2 (LOW)	53W	4900Lm
LTG3 (HIGH)	64W	6210Lm

**Color Temperature Pro-rate:**

CCT	OUTPUT
3000K	95%
3500K	97%
4000K	100%
5000K	103%

\*\*\*FOR ANY CUSTOM LED PACKAGE REQUESTS CONSULT FACTORY

**Details**

**Application Features:** Premium grade, surface mounted, high performance direct/indirect architectural luminaire with single perforated metal lamp shield. For use in indoor applications where a LED luminaire with soft, low-glare illumination and modern styling is required.

**Construction:** Die formed and spot welded, heavy guage cold rolled steel housing. Diffuser held within hinged door frame, hinges from either side using steel pin hinges and is held in closed position by two positive cam latches. Ballast accessed through tool-less ballast cover. Sufficient knock-outs provided for optional pendant stems.

**Electrical:** Integral driver.

**Approvals:** Union made, ETL listed, and manufactured in the US.

**Mounting:** Surface mounts over electrical junction box or with optional pendant stems.

**Optics:** Contoured reflector and perforated shield with opal white acrylic overlay.

**Options:** Emergency Battery Backup, Dimming, and 6' Whips.

