



DATE

JOB NAME

TYPE

Features	Applications
<ul style="list-style-type: none"> <li>• Great for perimeters</li> <li>• 91.4% efficient</li> <li>• Available in T5/T5HO lamps or with LED module</li> <li>• Comes standard with specular aluminum asymmetrical reflector and steel housing</li> </ul>	<ul style="list-style-type: none"> <li>• Office Areas</li> <li>• Retail Stores</li> <li>• Class Rooms</li> <li>• Libraries</li> <li>• Restaurants</li> </ul>

Series	Size	Lamps	Watts	Voltage	Options
CV1S	2FT 3FT 4FT 6FT 8FT	1 2 LED Boards	14W T5 24W T5HO 21W T5 39W T5HO 28W T5 54W T5HO 35W T5 80W T5HO 28W T5-8 (Tandem) 54W T5HO-8 (Tandem) (Consult Factory for LED module watt and lumen info)	120 277 UNV	EM—EM Pack DB—Dimming Ballast WR-White Reflector

Ordering Example: CV1S-4FT-2-54WT5HO-UNV-EM

**Details**

**Application Features:** Specification grade cove lighting fixture. For use in indoor applications where a T5, T5HO, or LED cove light is required. Available in lengths

**Construction:** Die and brake formed, 20 ga. pre-painted white cold rolled steel housing. Aluminum specular silver reflector. Sufficient knock-outs are provided for convenience outlet, pull switch and flexible conduit attachment.

**Finish:** Pre-painted high reflective white.

**Electrical:** Electronic ballasts are class P, thermally protected.

**Approvals:** UL Listed and manufactured in the US

**Options:** Emergency Battery Backup, Dimming Ballast, and High-Reflectance White Optics Reflector

