

DATE _____ PROJECT _____ FIRM _____ TYPE _____



FEATURES

- Damp Location Rated
- CRI 90+ Standard; R9>50
- 5 Year, 50,000 Hour Fixture Warranty
- 2700K, 3000K, 3500K, 4000K & 5000K Color Temperatures Available
- Available with PoE- [See More](#)

APPLICATIONS Offices, Lobbies, Retail Stores, Classrooms, Reception Areas, & Corridors

FINISH Standard Powder-Coated White. Custom RAL Colors Available

CONSTRUCTION Heavy Gauge, Cold Rolled Steel Housing

OPTICS Frosted Acrylic Diffuser

FIXTURE RATINGS & CERTIFICATIONS Union Made ETL Listed Made In The USA Damp Location Rated




DRIVERS, SENSORS, & POE



For Wiring Diagrams, POE, and Sensor Information Click [Here](#)

ELECTRICAL Integral Driver with 0-10V Dimming Standard. Several Driver Options Available

EXTRUSION DIMENSIONS



LED SYSTEM INFORMATION

	Nominal System Watts	Nominal Delivered Lumens	Nominal Efficacy
Standard (LTG1)	29 W	2,755 lm	95 LPW
Low (LTG2)	20 W	1,957 lm	97 LPW
High (LTG3)	40 W	3,686 lm	92 LPW

Based on a 90CRI, 3500K luminaire using one driver. Custom outputs available; specify below.

ORDERING



<p>1 - FIXTURE ID KSRI LED</p>	<p>2 - LENGTH 2x2</p>	<p>3 - COLOR TEMP 27 - 2700K/90 CRI 30 - 3000K/90 CRI 35 - 3500K/90 CRI 40 - 4000K/90 CRI 50 - 5000K/90 CRI WD* - Warm Dim 2200K-3000K TW** - Tunable White 2700K-6500K RGBW30*** - RGB + 3000K RGBW35*** - RGB + 3500K *Requires WD10 Driver **Requires DMX or TW10 Driver ***Requires DMX Driver</p>	<p>4 - LED SYSTEM LTG1 - Standard LTG2 - Low LTG3 - High LTGC - Custom Output</p>	<p>5 - VOLTAGE UNV - Universal (120/277V) 347V* - 347V *Must use DB Driver</p>	<p>6 - DRIVER DB - Standard 1% Dimming (0-10V) DB.1% - 0.1% Dimming (0-10V) ELV-TRI - 2-wire 1% Dimming (120V only) ELV and TRIAC Compatible LDE1 - Lutron Digital EcoSystem LDE5 - 5 Series EcoSystem; 5% Dimming DALI - DALI-2 Driver PoE - Power over Ethernet. Consult Factory for Compatibility DMX - For Color Tuning and RGBW (Remote) TW10 - Dual Channel, 0-10V For Color Tuning (CCT and Intensity Control) WD10 - 0-10V Driver For Warm Dimming</p>	<p>7 - FINISH W - White (Standard) CC - Custom Color (provide RAL#)</p>	<p>8 - MOUNTING T - 9/16" Tee Grid T15 - 15/16" Tee Grid SG - Slot Grid/Interlude F - Flange</p>	<p>9 - CIRCUIT (Optional) EM 120V - Emergency Pack EM 277V - Emergency Pack DC-X* - Dual Circuit with Static Color *X denotes specified color (ie DC-BLUE). Consult Factory</p>	<p>10 - OTHER OPTIONS WH6 - 6ft Whips Preinstalled AR - Air Return</p>
---	----------------------------------	--	--	---	---	---	---	--	--