



DATE

JOB NAME

TYPE

Features	Applications
<ul style="list-style-type: none"> • Shallow profile providing continuous light • Regressed opal white lens • Uses T8, T5, or T5HO 	<ul style="list-style-type: none"> • Offices Areas • Corridors • Libraries • Perimeters

Series	Size	Lamps	Watts	Voltage	Mounting	Options
LS4 RG	4FT (NOMINAL) 8FT (NOMINAL) 12FT (NOMINAL) XFT (CONTINUOUS ROW MOUNTING)	1 2 (T5/T5HO ONLY)	T5 T5HO T8	120 277 UNV	AC-Aircraft Cable (24", 36" standard, 48") PS-Pendant Stem (6", 12", 24", 36", 48") SM-Surface Mount WB-Wall Bracket (with uplight slots)	EM-Emergency pack EM2- 2 light emergency pack DB-Dimming Ballast SC-Separate Circuit WW-Wall Wash Reflector UP- 100% Uplight CC-Custom Color

Ordering Example: LS4 RG-8FT-1-T5HO-UNV-PS12"-EM

Details

Application Features: Premium grade, modular architectural luminaire. For use in indoor applications where a T8, T5, T5HO or LED luminaire with small profile providing continuous light is required. Available as individual fixtures or with end and intermediate units for mounting in continuous rows. Removing endplates allow for diagonally overlapping lamps providing uniform light without socket shadows. Available in 4', 6' and 8' lengths. Available in suspended, surface or wall mounted configurations.

Construction: Aluminum Alloy 6063 with opal acrylic lens. Sufficient knock-outs provided for connections and through wiring.

Finish: Powder painted high reflectance white.

Electrical: Electronic ballasts are class P, thermally protected.

Approvals: Union made, UL listed, and manufactured in the US.

Light Distribution:
 Indirect-0% Direct-100%

Optics: White reflector with regressed Opal white acrylic lens

Options: Emergency Battery Backup, Dimming Ballast, Separate Circuit, Wall Wash Reflector, or custom color.

