

S LED (STANDARD STRIP)

coronet



DATE

JOB NAME

TYPE

Features Applications

- Fixture components snap together for ease of installation and maintenance
- Knock-outs provided for convenience outlet, pull switch and conduit attachment

- Office Areas
- Retail Stores
- Class Rooms
- Libraries
- Restaurants

| Series | Size | LED System | Color Temp | Voltage | Options |
|--------|------|---|---|-------------------|--|
| S LED | 4FT | LTG1- Standard LTG2- Standard LTG3- Standard C- Custom Package (ie-C5000Lm) | 2700K 3000K 3500K 4000K 5000K | 120 277 UNV | EM-EM Pack Lamp ASYM-Asymmetric Reflector LUTRON 2- Hi-Lume Dimming Driver (1% 2-wire control) LUTRON 3- Hi-Lume Dimming Driver (1% 3-wire control) |

Ordering Example: S LED-4FT-LTG1-4000K-UNV-ASYM

LED System Information

Options:

| NOMINAL PACKAGE | NOMINAL SYSTEM WATTS | NOMINAL DELIVERED LUMENS |
|-----------------|----------------------|--------------------------|
| LTG1 (STANDARD) | 35W (per 4ft) | 3,900Lm (per 4ft) |
| LTG2 (LOW) | 25W (per 4ft) | 2,950Lm (per 4ft) |
| LTG3 (HIGH) | 38W (per 4ft) | 4,260Lm (per 4ft) |

Color Temperature Pro-rate:

| CCT | OUTPUT |
|-------|--------|
| 2700K | 93% |
| 3000K | 95% |
| 3500K | 97% |
| 4000K | 100% |
| 5000K | 103% |

***FOR ANY CUSTOM LED PACKAGE REQUESTS CONSULT FACTORY

Details

Application Features: Specification grade fluorescent channel. For use in indoor applications where a LED striplight with tool-less design and low cost is required.

Construction: Die formed 20 ga. cold rolled steel housing. Fixture components snap together for ease of installation and maintenance. Sufficient knock-outs provided for convenience outlet, pull switch and flexible conduit attachment.

Finish: Baked white enamel.

Electronic: Integral Driver.

Approvals: Union made, UL listed, and manufactured in the US.

Options: Emergency Battery Backup, Dimming Ballast, Separate Circuit, Motion Sensor, Wireguard, Asymmetric Reflector, Symmetric Reflector.

