



(IMAGE SHOWN IS FOR "NT" MOUNTING FOR TRIMLESS SPACKLE FLANGE)

DATE

JOB NAME

TYPE

Features	Applications
<ul style="list-style-type: none"> • Maximum efficiency • Shallow design • Uses T5 or T5HO lamps, or dimmable LED modules 	<ul style="list-style-type: none"> • Hospitals & Clinics • Medical Offices & Labs • Office Areas • Retail Stores • Class Rooms

Series	Size	Lamps	Watts	Voltage	Mounting	Options
LSR3	4FT (Nominal) 6FT (Nominal) 8FT (Nominal) XFT (Custom Runs Available)	1 2	T5 T5HO	120 277 UNV	F-Flange NT-No Trim (spackle flange) T- Tee Grid* SG- Slot Grid**	EM-Emergency Pack DB-Dimming Ballast WH-6' Whips WW-Wall Wash

*Standard Tee is 9/16". Must specify if 15/16"
 **Fixture depth different for SG option; see page 2

Ordering Example: LSR3-4FT-1-54WT5HO-T-UNV-DB

Details

Application Features: Premium grade, recessed, modular architectural luminaire. For use in indoor applications where a T5, T5Ho or LED luminaire with small profile providing continuous light is required. Available as individual fixtures or with end and intermediate units for mounting in continuous rows. removing endplates allow for diagonally overlapping lamps providing uniform light without socket shadows.

Construction: Extruded aluminum housing. Sufficient knock-outs provided for connections and through wiring.

Finish: White powder coated finish.

Electrical: Integral Driver.

Approvals: UL Listed for damp location.

Mounting: Flange for sheetrock and grid ceiling installation or No Trim for spackle flange.

Optics: Satin Acrylic Snap-in Lens.

Options: Emergency Battery Backup, Dimming Ballast, 6' Whips.

