



DATE

JOB NAME

TYPE

Features **Applications**

- · Small profile providing continuous light
- Opal white lens
- · Wall Wash Reflector Optional
- · Uses T8, T5, T5HO lamps

- · Office areas
- Perimeters
- · Retail Stores
- Corridors
- · Class rooms
- Libraries

Series	Size	Lamps	Watts	Voltage	Mounting	Options
LSR4						
	2FT (NOMINAL) 4FT (NOMINAL) 6FT (NOMINAL) 8FT (NOMINAL) XFT (CUSTOM LENGTHS/RUNS)	1 2	T5 T5HO T8	120 277 UNV	F-Flange NT-No Trim (spackle flange) T- Tee Grid* (T5/T5HO Only) SG- Slot Grid (T5/T5HO Only)	EM-Emergency Pack EM2-Emergency Pack 2-lamp (T8 Only) DB-Dimming Ballast SC-Separate Circuit WW-Wall Wash reflector (Only Available with 1 Lamp) WH-6' Whips

Ordering Example: LSR4-4FT-1-28WT5-UNV-NT-WW

*Standard Tee is 9/16". Must specify if 15/16"

Details

Application Features: Premium grade, recessed, modular architectural luminaire. For use in indoor applications where a T8, T5, T5HO or LED luminaire with small profile providing continuous light is required. available as individual fixtures or with end and intermediate units for mounting in continuous rows. removing endplates allow for diagonally overlapping lamps providing uniform light without socket shadows. available in 2', 4', 6' and 8' nominal lengths.

Construction: Aluminum Alloy 6063 with opal acrylic lens. Sufficient knock-outs provided for connections and through wiring.

Finish: Powder painted high reflectance white.

Approvals: Union made, ETL listed, and manufactured in the US.

Mounting: Flange for sheetrock and grid ceiling installation or No Trim for spackle flange. Tee Grid and Slot grid not available in T8. Wall Bracket also available for wall mounting.

Optics: Opal white acrylic lens

Options: Emergency Battery Backup, Dimming Ballast, Separate Circuit, Wall Wash Reflector (Only Available with 1 Lamp), or Custom Color.









