



DATE

JOB NAME

TYPE

Features	Applications
<ul style="list-style-type: none"> • HID alternative or replacement • LED Hi-Bay Tube • High reflectance of light from the 95% enhanced specular aluminum reflector – standard • 50,000 Hour Lamp Life 	<ul style="list-style-type: none"> • High Bay Lighting • Warehouses • Manufacturing Areas • Gymnasiums

Series	Size	LED System	Color Temp	Voltage
HE HBA	4FT	LTG1- Standard LTG2- Low LTG3- High	4000K 5000K	120V 277V UNV

Ordering Example: HE HBA-4FT-LTG1-4000K-UNV

LED System Information

Options:

NOMINAL PACKAGE	NOMINAL SYSTEM WATTS	NOMINAL DELIVERED LUMENS
LTG1 (STANDARD)	200W	22,000Lm
LTG2 (LOW)	180W	20,000Lm
*LTG3 (HIGH)	220W	25,000Lm

Color Temperature Pro-rate:

CCT	OUTPUT
4000K	100%
5000K	103%

Details

Application Features: Mid-level, specification grade, high efficiency, high output LED fixture. Ideal fixture as an HID alternative.

Finish: Silver powder coated finish.

Construction: Aluminum & PC cover (available clear and milky).

Electrical: Integral Driver

Approvals: Approved to UL standards. IP65.

