


DATE	PROJECT	FIRM	TYPE
------	---------	------	------




Architectural luminaire with extremely low profile. For use in indoor applications where an LED luminaire with small profile providing continuous light is required. Comes standard with 100% direct light, available as 100% indirect (see options).

### FEATURES

- 100% Direct Light; 100% Uplight Optional
- Special Diffuse Acrylic Drop Lens With 260 Degree Distribution
- Damp Location Rated
- CRI 90+ Standard
- 3000K & 3500K Color Temperatures Available

<b>APPLICATIONS</b>	Offices, Lobbies, Retail Stores, Classrooms, Reception Areas & Corridors		
<b>CONSTRUCTION</b>	Extruded Aluminum Housing With Die Cast Aluminum End Caps	<b>OPTICS</b>	Satin PMMA Lens, No LED Imaging
<b>WARRANTY</b>	5 Year Limited Warranty (Covers Standard Components)	<b>FINISH</b>	Standard Powder-Coated Black. Custom RAL Colors Available
<b>FIXTURE RATINGS &amp; CERTIFICATIONS</b>	Union Made ETL Listed	Made In The USA Damp Location Rated	
<b>ELECTRICAL</b>	0-10V Remote Driver With 10% Dimming		

### EXTRUSION DIMENSIONS



### LED SYSTEM INFORMATION

	System Watts	Delivered Lumens
Standard (LTG1)	5 W/ft	205 Lm/ft
Low (LTG2)	3 W/ft	125 Lm/ft

Based on a 3500K luminaire using one driver. Please consult factory for custom lumen outputs & wattage.

<b>ORDERING</b>	1	2	3	4	5	6	7	8	9	10
<b>1 - FIXTURE ID</b>	<b>2 - LENGTH</b>		<b>3 - COLOR TEMP</b>		<b>4 - LED SYSTEM</b>		<b>5 - VOLTAGE</b>		<b>6 - DRIVER (Remote)</b>	
MILAN	2 - 2 ft 4 - 4 ft 8 - 8 ft 12 - 12 ft		30 - 3000K/90 CRI 35 - 3500K/90 CRI		LTG1 - Standard LTG2 - Low		UNV - Universal (120/277V)		DB - Standard 10% Dimming (0-10V)	

<b>7 - FINISH</b>	<b>8 - MOUNTING</b>	<b>9 - OPTICS</b>	<b>10 - CIRCUIT (Optional)</b>
BLK - Black (Standard) W - White CC - Custom Color (provide RAL#)	AC - Aircraft Cable (50") SM - Surface Mount WM - Wall Mount	SD - Standard Diffuser	EM 120V - Emergency Pack EM 277V - Emergency Pack

DATE

PROJECT

FIRM

TYPE

## MOUNTING

SM - Surface Mount

