


DATE	PROJECT	FIRM	TYPE
------	---------	------	------




Architectural luminaire with extremely low profile. For use in indoor applications where an LED luminaire with small profile providing continuous light is required. Comes standard with 100% direct light, available as 100% indirect (see options).

FEATURES

- 100% Direct Light; 100% Uplight Optional
- Special Diffuse Acrylic Drop Lens With 260 Degree Distribution
- Damp Location Rated
- CRI 90+ Standard
- 3000K & 3500K Color Temperatures Available

APPLICATIONS	Offices, Lobbies, Retail Stores, Classrooms, Reception Areas & Corridors		
CONSTRUCTION	Extruded Aluminum Housing With Die Cast Aluminum End Caps	OPTICS	Satin PMMA Lens, No LED Imaging
WARRANTY	5 Year Limited Warranty (Covers Standard Components)	FINISH	Standard Powder-Coated Black. Custom RAL Colors Available
FIXTURE RATINGS & CERTIFICATIONS	Union Made ETL Listed	Made In The USA Damp Location Rated	
ELECTRICAL	0-10V Remote Driver With 10% Dimming		

EXTRUSION DIMENSIONS



LED SYSTEM INFORMATION

	System Watts	Delivered Lumens
Standard (LTG1)	5 W/ft	205 Lm/ft
Low (LTG2)	3 W/ft	125 Lm/ft
High (LTG3)	8.75 W/ft	365 Lm/ft

Based on a 3500K luminaire using one driver. Please consult factory for custom lumen outputs & wattage.

ORDERING	1	2	3	4	5	6	7	8	9	10
1 - FIXTURE ID	MILAN									
2 - LENGTH	2 - 2 ft		4 - 4 ft		8 - 8 ft		12 - 12 ft			
3 - COLOR TEMP	30 - 3000K/90 CRI		35 - 3500K/90 CRI							
4 - LED SYSTEM	LTG1 - Standard		LTG2 - Low		LTG3 - High		C - Custom Output (ie-C550Lm/ft)			
5 - VOLTAGE	UNV - Universal (120/277V)									
6 - DRIVER (Remote)	DB - Standard 10% Dimming (0-10V)									

7 - FINISH	8 - MOUNTING	9 - OPTICS	10 - CIRCUIT (Optional)
BLK - Black (Standard) W - White CC - Custom Color (provide RAL#)	AC - Aircraft Cable (50") SM - Surface Mount WM - Wall Mount	SD - Standard Diffuser	UP - All Uplight (Fixture Inverted) EM 120V - Emergency Pack EM 277V - Emergency Pack

DATE

PROJECT

FIRM

TYPE

MOUNTING

SM - Surface Mount

