



DATE

JOB NAME

TYPE

Features	Applications
<ul style="list-style-type: none"> • Glare-free downlight • 60% Indirect/ 40% Direct distribution • Can be suspended or surface mounted 	<ul style="list-style-type: none"> • Offices • Lobbies • Corridors • Retail Stores

Series	Size	Lamps Down	Lamps Up	Watts	Voltage	Mounting	Options
LS3	2FT (Nominal) 3FT (Nominal) 4FT (Nominal) 6FT (Nominal) 8FT (Nominal) XFT (Continuous Row Mounting)	1DN 2DN	1UP 2UP	T5 T5HO	120 277 UNV	AC-Aircraft Cable (24", 48") SM-Surface Mount WB-Wall Bracket	EM-Emergency Pack* (*Must specify voltage) EM2-2 Light Emergency* (*Must specify voltage) DB-Dimming Ballast SC-Separate Circuit CC-Custom Color UP- 100% uplight

Ordering Example: LS3-4FT-1DN-1UP-28T5HO-SM-UNV-SC

Details

Application Features: Premium grade, modular architectural luminaire. For use in indoor applications where a T5, T5HO providing continuous light is required. Available as individual fixtures or with end and intermediate units for mounting in continuous rows. Available in suspended, surface or wall mounted configurations. *****Lamping configuration varies. Please consult factory.**

Construction: Extruded aluminum housing. Hanging points for continuous rows vary-please consult factory.

Finish: White powder coated finish

Electrical: Electronic ballasts are class P, thermally protected.

Light Distribution:
 Indirect-0%. Direct-100%
 or Indirect-60%. Direct-40%

Approvals: Union made, UL listed, and manufactured in the US.

Optics: Opal white Snap-In Lens.

Options: Emergency Battery Backup, Dimming Ballast, Uplight

